

EASY LAB



TECHNICAL DATASHEET

GRISEUR FIR TREE FOR NEW OR OLD WOOD 0849 MANUAL APPLICATION

**FOR FURNISHED FLATS, WOODWORK, PARQUETS,
PANELLINGS, CHALETS
OUTSIDE – INSIDE**

A single application yields a grey patina by oxidation on coniferous wood and not tannic wood. We can use it on little tannic oaks.

PREPARATION

NEW WOOD: the wood must be sanded and dusted. He can be brushed with an abrasive brush so as to use the soft veins.

OLD WOOD: the wood must be sanded, more have no track of varnish, wax and dust it.

IMPLEMENTATION

To mix 150 g either 100 g or 50 g of powder according to the wished color ((3, 2 or 1 firmly packed measures) in 1 liter of water, indeed to mix, let rest 5 - 10 mn.

APPLICATION

Applies by spraying or to the brush in plentiful and regular coats, after drying one eliminate the coat of white dust by means of a green abrasive or of a mono-brush provided with a PAD, We can apply this product to any temperature of $0 > 30^{\circ}$, the drying can be made in the TUNNEL, there is no modification of color.

After drying, we brush and inhale. (Brush Nylon not abrasive).

Wood are ready to receive a finish. It is possible to clear this color by applying some powder to clear 0698 (see FT).

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21, rue André Chénier 69120 Vaulx en Velin (Grand Lyon) - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail : easylab@easylabfinish.com

Internet : www.easylabfinish.com - RCS LYON B 349 783 712 00046 - NAF : 245 C

EASY LAB



TECHNICAL DATASHEET

Finish

Wood so prepared can receive a finish, but if we wish to preserve this light gray color, we propose you the INSULATING BOTTOM 0219 which will allow you quite typical of varnish without changing the color.

For the outside, we propose you our oil for chalets UV matt ANTI 07701.

Adjust

We propose you more or less oxidizing powders according to the quality of wood and wished result.

0849 - 0849/1 - 0849/2 - 0849/3

They will allow you to choose the powder the best adapted to your wood.




Application rate

7 - 9 m² in approximately the liter according to the porosity of the ground.

Packaging

➤ 600 Gr = 4 L - 5 Kg = 33 L – 30 Kg = 200 L.

SAFETY

-  It is indispensable to wear rubber gloves
-  Do not swallow
-  Keep out of the reach of children

This information is given here in good faith but does not involve our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21, rue André Chénier 69120 Vaulx en Velin (Grand Lyon) - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail : easylab@easylabfinish.com

Internet : www.easylabfinish.com - RCS LYON B 349 783 712 00046 - NAF : 245 C

EASY LAB



TECHNICAL DATASHEET

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21, rue André Chénier 69120 Vaulx en Velin (Grand Lyon) - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail : easylab@easylabfinish.com

Internet : www.easylabfinish.com - RCS LYON B 349 783 712 00046 - NAF : 245 C