



TECHNICAL DATA SHEET

Oil for parquet floors

Aqueous colorless

Does not alter or darken wood which has been treated with graying agent
The color does not change

0218

This oil emulsion does not contain any COV – it gives a quality finish while maintaining a natural aspect.

Preparation

Wood which has been treated or not with our graying agent, must be dry, sanded down and dust free.

Application

It may be used on all woods for indoor use and is applied in one or two coats. The second coat should be applied wet on wet (a second coat applied on a very dry first coat will not adhere well nor stretch properly). On very hard woods the first coat may be diluted by 10% with water.

“Shake well before using”

Used by hand

It should be applied either with a brush or rolled on in a fine and regular coat.

Industrial use

It can be rolled on or sprayed.

Finish

Once it has dried a nice finish can be obtained with a WHITE PAD which will give the wood a nice appearance.

- ✚ Cleaning of tools: with water
- ✚ Quantities : 8 – 10 m² per liter depending on how porous the wood is
- ✚ Packaging: 1 liter, 5 liters, 30 liters and more.

Security measures

- ✚ It is indispensable to wear rubber gloves
- ✚ Do not swallow
- ✚ Keep out of the reach of children

This information is given here in good faith but does not involve our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21, rue André Chénier 69120 Vaulx en Velin (Grand Lyon) - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail: easylab@easylabfinish.com

Internet: www.easylabfinish.com - RCS LYON B 39 783 712 00046 - NAF: 245 C